



### MODEL AB

AB Automatic Balancing Valve is a combination ball valve, automatic flow control device and union. The removable flow cartridge limits GPM to within  $\pm 5\%$  of specified flow. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include Adjustable Memory Stop and Dual Pressure/ Temperature Ports.

### MODEL SV

SV Combination Strainer Valve is a combination ball valve, wye strainer and union. The 20 mesh S/S strainer screen is removable for cleaning. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include Pressure/Temperature Port, Hose End Drain Valve and plugged Bypass Port.

### MODEL URP

URP Union is an O-ring sealed union with vent and pressure/temperature measurement. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available. Standard features include "PTV" Combination Pressure/Temperature Vent.

### MODEL UB

UB Union is a O-ring seal union with plugged accessory ports. Fixed End connection available in FNPT or SWT. Tailpiece connection available in MNPT, FNPT or SWT. Size reductions available.

QUANTITY	SIZE	GPM	TAG

